
LAQUAFORCE

PROFINE® RED DIRT AND SAND FILTRATION









Profine[®] filter cartridge

Red is the first step!

Remove the turbidity of Water.

No more sediments or foreign particles in suspension.

The **Red** Cartridge (extruded polypropylene) ensures filtration up to 5 microns.

The first essential step to having clean drinking water

Features

- PROFINE[®] RED reduces turbidity as well as suspended particles with a filter rating of 5 microns
- This is a quick-connect cartridge with extruded polypropylene.
- The cartridge is in compliance with EU Directive 93/83/EC for use in processing systems and/or household appliances.

Dimensions

External diameter: 87.4 mm Small cartridge height: 269 mm Medium cartridge height: 384 mm Large cartridge height: 529 mm

A.P.Laquaforce Services Ltd

Agathonos 9, Ypsonas – Limassol T: 7777 2782 – F:+357 25755540 www.laquaforce.com – info@laquaforce.com



TECHNICAL SPECIFICATIONS

	SMALL	MEDIUM	LARGE
Function flow rate	3 l/min *	5 l/min *	7 I/min *
Working pressure	Min. 29 – Max. 87 Psi	Min. 29 – Max. 87 Psi	Min. 29 – Max. 87 Psi
	Min. 4 Max. 30°C	Min. 4 Max. 30°C	Min. 4 Max. 30°C
Temperature	(39-86°F)	(39-86°F)	(39-86°F)
Capacity	Until clogging	Until clogging	Until clogging

CARTRIDGE REPLACEMENT INSTRUCTIONS

Gen D			C. S.
Close the water inlet valve and open the outlet valve.	Turn the cartridge a ¹ / ₄ turn to the left and pull it out.	Remove the cap seal and moisten the O- rings with water. Push the cartridge up and turn it a ¹ / ₄ turn to the right.	Open the water inlet valve and allow the water to run for 5 minutes before taking any water

A.P.Laquaforce Services Ltd

Agathonos 9, Ypsonas – Limassol T: 7777 2782 – F:+357 25755540 www.laquaforce.com – info@laquaforce.com