

AUTOTROL® 255/760C – 25L RESIDENTIAL SOFTENER



Benefits

- Complete removal of scale (Ca⁺⁺ and Mg) from water
- Protects house plumbing and boiler elements
- Prolongs the life of taps and mixers
- Economy on electricity bill due to better efficiency of boiler and washing appliances
- Saves money on cleaning chemicals and soaps
- Less chemicals guarantee a better and safer environment
- Less time cleaning and trying to remove scale
- Eco friendly – Only uses 3 Watt average power consumption

Technical

Dimensions: H:113 cm x W:33 cm x D:65 cm

Full auto (Volumetric Controlled and Time Controlled regeneration of the softener)

Digital display

Clever microprocessor to save salt usage by controlling regeneration according to the water used during the last 4 weeks

25 Liters of food grade Ion exchange resin

Inlet/Outlet diameter: 1"

Operating pressure 2 to 7 bar. Pressure tested to 15 bar

Capacity: 165 m³/ 10ppm CaCO₃

Salt consumption per regeneration 4.5 kg

85 liters brine tank capacity

Hard water mixing valve to adjust output hardness

Super capacitor for keeping time of day during power outage

Programming stored in memory and not lost during power outage

Internal bypass automatically provides water during regeneration

Optional: Chlorination and check salt indication module to disinfect and protect the softening resin from bacteria growth



TESTED and CERTIFIED by the WQA to NFS/ANSI Standard 44 for Water Softener Performance.



TESTED and CERTIFIED by the WQA to NFS/ANSI Standard 61 Section 8 Material Safety Only.



TESTED and CERTIFIED by the WQA to NFS/ANSI Standard 372 for Lead Free Compliance.



Restriction of Hazardous Substance Compliant