## LAQUAFORCE

## **RX® F79B-LCD** 4.5L VOLUME CONTROLLED SOFTENER





## Benefits

- Complete removal of scale (Ca<sup>++</sup> and Mg) from water
- Protects plumbing and boiler elements
- Prolongs the life of dishwashers
- Economy on electricity bill due to better efficiency of boiler and washing appliances
- Saves money on cleaning chemicals and soaps
- Less chemicals guarantee a better and safer environment
- Less time cleaning and trying to remove scale
- Eco friendly Only uses 3 Watt average power consumption
- Compact design with integrated brine tank

## **Technical**



Dimensions: H:45cm x W:22 cm x D:37 cm
7 x 13 pressure tank
Digital display
Clever microprocessor to save salt usage by controlling regeneration according to the water used during the last 4 weeks
4.5 Liters of food grade lon exchange resin
Salt consumption: 0.6 kg/regen
Max. flow rate: 1.8 m<sup>3</sup>/hour
Inlet/Outlet diameter: 3/4"
Drain line diameter: 1/2"
Operating pressure 2 to 7 bar. Pressure tested to 15 bar
Capacity: 23 m<sup>3</sup>/ 10ppm CaCO<sub>3</sub>
10 liters brine tank capacity

Hard water mixing valve to adjust output hardness

Programming stored in memory and not lost during power outage Internal bypass automatically provides water during regeneration

> A.P. Laquaforce Services Ltd 9 Agathonos street, 4189 Ipsonas, Lemesos T: 7777 2782 – F:+357 397160 www.laquaforce.com – info@laquaforce.com